



## GENERAL SPECIFICATIONS

Extruded inner core made of natural or black antistatic PTFE.  
 Outer reinforcement: one AISI 304L wire braid with high tensile strength.  
 External braid in Technora® fiber (non conductive para-aramid fiber).

## OPTIONS

| Customized sizes.

INTERNAL DIAMETER		WALL THICKNESS	OUTER DIAMETER	MINIMUM BEND RADIUS	MAXIMUM WP	MINIMUM BP
DN	mm	mm	mm	mm	bar at 23°C	bar at 23°C
10	9.50	0.70	13.40	60	135	540
13	12.7	0.70	16.70	90	120	480



All our hoses are developed first for static application. Maximum WP (Working Pressures) calculated using a Safety Factor of 4. To guarantee quality and reliability of our products, all PTFE inner cores are tested under pressure.

## TEMPERATURE SERVICE

- 70°C + 260°C (PTFE)  
 - 200°C + 250°C (TECHNORA® FIBER)  
 (at these temperatures maintains more than half of its room-temperature tensile strength. It has a long-term dimensional stability and excellent resistance to corrosion)

PTFE WORKING TEMPERATURE	PRESSURE DE-RATING %
Up to 130 °C	100%
150°C	85%
180°C	65%
200°C	50%
220°C	30%
260°C	10%

## APPLICATIONS

Chemical, foodstuffs, steam, gases, detergents, refrigerants and any application focused on the transfer of fluids and gases under critical usage conditions and in severe environments.



Values and coefficients contained in this sheet are for information only and shall in no event be held to constitute or imply any warranty, undertaking, express or implied commitment. No liability whatsoever can be accepted by ITG SRL with respect to difference to the values reported in the tables or misuse by the Customer of the product.