

GENERAL SPECIFICATIONS

Extruded inner core made of natural PTFE.

Outer reinforcement: one AISI 304L wire braid with high tensile strength.

External cover in PU (poliuretane).

OPTIONS

| Branding feasibility on the PU jacket.



INTERNAL DIAMETER		WALL THICKNESS	OUTER DIAMETER	MINIMUM BEND RADIUS	MAXIMUM WP	MINIMUM BP
DN	mm	mm	mm	mm	bar at 23°C	bar at 23°C
3	2.90	0.65	6.50	20	225	900



All our hoses are developed first for static application. **Maximum WP (Working Pressures)** calculated using a Safety Factor of 4. To guarantee quality and reliability of our products, all PTFE inner cores are tested under pressure.

TEMPERATURE SERVICE

- 60°C + 260°C (PTFE)

- 20°C + 80°C (TPU)

APPLICATIONS

High performances hose for bikes brake systems.

PTFE WORKING TEMPERATURE	PRESSURE DE-RATING %
Up to 130 °C	100%
150°C	85%
180°C	65%
200°C	50%
220°C	30%
260°C	10%



Values and coefficients contained in this sheet are for information only and shall in no event be held to constitute or imply any warranty, undertaking, express or implied commitment. No liability whatsoever can be accepted by ITG SPA with respect to difference to the values reported in the tables or misuse by the Customer of the product.